

CONFIGURATION

Configuration standard and on request.

SPIRALS

In steel; models available on [Layout](#) page

LIGHTING

LED

GRAPHIC DISPLAY

Programmable in different languages with various spot possibilities, Programmable stand-by.

CHILLER

Compact chiller for quick and easy extraction. Ecological refrigeration Gas R290. Internal Temperature 8°C with external temperature at 32°C.
3°C Version.
Optional Quiet Chiller.
Programmable Stand-by

FRONT GLASS

Excellent product visibility

TECHNOLOGY

Telemetry; applicable internet Modem; EVA-DTS, GPE DATA (software updating by PC)

PAYMENT SYSTEM

Executive – MDB; predisposed for latest generation payment systems (credit card, Paypal,...)



DIMENSIONS

HEIGHT	183 cm
WIDTH	72 cm
DEPTH	82,5 cm
WEIGHT	190 kg

ELECTRIC POWER SUPPLY ABSORBED POWER

230V +/- 10%
Also possible in 110V version

Standard Version
Average annual consumption: 1433 KWh
3° Version
Average annual consumption: 2270 KWh



www.asl-luebeck.de
Heiß-/Kalt-, Snackautomaten
Produkthandel und Service

Reepschlägerstraße 11 a, 23556 Lübeck
Tel. 0451/880 48 80 • Fax 880 48 81